



STPXXXS – B72/Pnhg

-455W 20.9%

| | | | | |
|-------|---------|------|------|---|
| 20.9% | ↓ | | | |
| 2% | | 3800 | 5400 | * |
| | E Harsh | | | |

**

IEC 61730
IEC 61215

ISO 9001
ISO 14001
ISO 45001



STPXXXS - B72/Pnhg 435-455W

144 (6 × 24)

STP-XC4

IP68

-40 ° C - +85 ° C

1500 V DC (IEC)

20 A

0/+5 W

(70 ± 5)%

2125 × 1130 × 1205
814

| STP455S-B72/Pnhg | | STP450S-B72/Pnhg | | STP445S-B72/Pnhg | | STP440S-B72/Pnhg | | STP435S-B72/Pnhg | |
|------------------|-------|------------------|-------|------------------|-------|------------------|-------|------------------|-------|
| STC | NMOT |
| 455 | 343.1 | 450 | 339.4 | 445 | 335.8 | 440 | 332.7 | 435 | 328.9 |
| 41.6 | 38.4 | 41.4 | 38.2 | 41.2 | 38.0 | 41.0 | 37.8 | 40.8 | 37.7 |
| 10.94 | 8.94 | 10.87 | 8.89 | 10.81 | 8.84 | 10.74 | 8.78 | 10.67 | 8.73 |
| 49.4 | 46.3 | 49.2 | 46.2 | 49.0 | 46.0 | 48.8 | 45.8 | 48.6 | 45.7 |
| 11.67 | 9.42 | 11.61 | 9.37 | 11.54 | 9.31 | 11.47 | 9.25 | 11.40 | 9.20 |
| 20.9 | | 20.7 | | 20.4 | | 20.2 | | 20.0 | |

2

2

+/- 3%

(455S)

| | 5% | 15% | 25% |
|-----|-------|-------|-------|
| STC | 467.3 | 511.8 | 556.3 |
| | 41.2 | 41.2 | 41.3 |
| | 11.35 | 12.43 | 13.51 |
| | 49.0 | 49.0 | 49.1 |
| | 12.12 | 13.27 | 14.43 |
| | 21.4 | 23.5 | 25.5 |

42 ± 2 ° C

-0.36%/° C

-0.304%/° C

0.050%/° C

